



Poly-kote is a high performance polymer-modified 2 coat masonry paint that can be roller, brush or spray-applied directly onto brick, block, render or pebble dash. Previously marketed as MR S6 masonry paint, Poly-kote has a proven track record of use that stretches back over 20 years.

Key Features

Poly-kote is a high performance masonry paint that can be applied onto virtually any masonry substrate:

- Fire performance: Class 0 surface spread of flame
- Provides a watertight finish that is vapour permeable when cured
- Smooth and durable finish
- Dirt repellent formulation
- Algae resistant and flexible masonry paint

Poly-kote is often specified in conjunction with Alumasc Polymer Renders:

- MR S4 – as part of an External Wall Insulation (EWI) system; or
- MR S5 – as part of a render only application.

Coverage Rate
c. 0.45 l/m² (based on 2 coat application)

Thickness
Nominal

Unit of Supply
10 litre drum

Weight
c. 15 kg / drum

Fire Performance
Class 0 spread of flame

Application
Roller, brush or spray applied

Mixing Ratio
Pre-mixed & ready for use.
First coat may be diluted by 10% v/v

Poly-kote is available in a standard range of colours. Other colours available upon request (subject to minimum order quantities).



MAGNOLIA




CREAM



SANDSTONE



MUSHROOM




GREY



BROWN



RED



WHITE

